

Revision Date: 06/11/2019

SAFETY DATA SHEET

1. Identification

Product identifier: CLAIRE DISINFECTANT SPRAY Q

Other means of identification

SDS number: RE1000038701

Recommended restrictions

Product Use: Disinfectant

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: CLAIRE MANUFACTURING COMPANY

Address: 1000 Integram Dr

Pacific, MO 63069

Telephone: 1-630-543-7600

Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Specific Target Organ Toxicity - Category 2

Repeated Exposure

Label Elements

Hazard Symbol:



Signal Word: Danger



Revision Date: 06/11/2019

2/19

Hazard Statement: Extremely flammable aerosol.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the

workplace. Do not breathe dust/fume/gas/mist/vapors/spray.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. Get medical advice/attention if you feel unwell. Specific treatment (see on this

label). Wash contaminated clothing before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Ethanol	64-17-5	10 - <20%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	10 - <20%
Propane	74-98-6	1 - <5%
Butane	106-97-8	1 - <5%
Glycine, N,N'-1,2- ethanediylbis[N- (carboxymethyl)-, sodium salt (1:4)	64-02-8	1 - <3%
2-Propanol, 2-methyl-	75-65-0	0.1 - <1%
Quaternary ammonium compounds, C12-14-alkyl[(ethylphenyl)methyl]dimet hyl, chlorides	85409-23-0	0.1 - <0.25%
2,6-Octadienal, 3,7-dimethyl-	5392-40-5	0.1 - <1%
Sodium hydroxide (Na(OH))	1310-73-2	0.1 - <1%
Ethanol, 2-butoxy-	111-76-2	0 - <0.1%
Ammonium hydroxide ((NH4)(OH))	1336-21-6	0 - <0.1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. SDS US - RE1000038701



Revision Date: 06/11/2019

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly

clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an

allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures



Revision Date: 06/11/2019

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures:

Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Aerosol Level 1

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Ethanol	TWA PEL	1,000 ppm 1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	REL	1,000 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1,000 ppm 1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (2009)
	AN ESL	1,880 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	10,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	1,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	18,800 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ethanol, 2-(2-butoxyethoxy)-	ST ESL	670 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11



Revision Date: 06/11/2019

	T			2016)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		67 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ethanol, 2-(2-butoxyethoxy) Inhalable fraction and vapor.	TWA	10 ppm		US. ACGIH Threshold Limit Values (03 2013)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm	1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	800 ppm	1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL		3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	800 ppm	1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		66,000 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
2-Propanol, 2-methyl-	TWA	100 ppm	300 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	450 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		20 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		62 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		620 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	150 ppm	450 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	300 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	100 ppm	300 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2008)
_	STEL	150 ppm	450 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	150 ppm	450 mg/m3	US. California Code of Regulations, Title 8,



Revision Date: 06/11/2019

				Section 5155. Airborne Contaminants (09
				2006)
	TWA PEL	100 ppm	300 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	REL	100 ppm	300 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
2,6-Octadienal, 3,7-dimethyl- - Inhalable fraction and vapor.	TWA	5 ppm		US. ACGIH Threshold Limit Values (01 2010)
2,6-Octadienal, 3,7-dimethyl-	ST ESL		50 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		310 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		31 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		5 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11
Sodium hydroxide (Na(OH))	Ceiling		2 mg/m3	2016) US. ACGIH Threshold Limit Values (2008)
Godium nydroxide (Nd(OH))	Ceiling		2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
	Ceil_Time		2 mg/m3	(1989) US. NIOSH: Pocket Guide to Chemical
	PEL		2 mg/m3	Hazards (2005) US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000) (02 2006)
	Ceiling		2 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	Ceiling		2 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
Sodium hydroxide (Na(OH)) - Particulate.	AN ESL		2 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		20 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ethanol, 2-butoxy-	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm	120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	5 ppm	24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm	240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	20 ppm	97 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	25 ppm	120 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		760 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		3,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,900 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ammonium hydroxide ((NH4)(OH))	AN ESL		92 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		180 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	35 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm		US. ACGIH Threshold Limit Values (2008)



Revision Date: 06/11/2019

TWA PEL	25 ppm	18 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
STEL	35 ppm	27 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
STEL	35 ppm	27 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
STEL	35 ppm	27 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
REL	25 ppm	18 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
PEL	50 ppm	35 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
time: End of shift.)		

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to

maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels

to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Avoid contact with eyes. Observe good industrial hygiene practices. When

using do not smoke. Contaminated work clothing should not be allowed out

of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.



Revision Date: 06/11/2019

Odor threshold:

pH:

No data available.

No data available.

No data available.

Initial boiling point and boiling range:

No data available.

Flash Point: -104.44 °C

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

No data available.

Vapor pressure: 5,171.0680 - 6,550.0194 hPa (20 °C)

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:

Solubility (other):

No data available.

No data available.

No data available.

No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.



Revision Date: 06/11/2019

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 16,286.29 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Ethanol LD 50 (Rabbit): 17,100 mg/kg

Ethanol, 2-(2- LD 50 (Rabbit): 2,764 mg/kg

butoxyethoxy)-

Glycine, N,N'-1,2- LD 50: > 2,000 mg/kg

ethanediylbis[N-(carboxymethyl)-, sodium

salt (1:4)

2-Propanol, 2-methyl- LD 50: > 2,000 mg/kg

2,6-Octadienal, 3,7- LD 50 (Rat): > 2,000 mg/kg

dimethyl-

Inhalation

Ethanol, 2-butoxy- LD 50 (Rabbit): 667 mg/kg

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Ethanol LC 50 (Rat): 124.7 mg/l

Ethanol, 2-(2- LC 50 (Various): > 20 mg/l

butoxyethoxy)-

Propane LC 50 (Mouse): 1,237 mg/l

Butane LC 50 (Mouse): 1,237 mg/l



Revision Date: 06/11/2019

Glycine, N.N'-1.2ethanedivlbis[N-

(carboxymethyl)-, sodium

salt (1:4)

2-Propanol, 2-methyl-LC 50: < 20 mg/l

Quaternary ammonium compounds, C12-14alkyl[(ethylphenyl)methyl] dimethyl, chlorides

LC 50: > 5 mg/lLC 50: > 20 mg/l

LOAEL (Rat): 30 mg/m3

Ethanol, 2-butoxy-LC 50: < 5 mg/l

LC 50: < 20 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Ethanol NOAEL (Rat(Male), Oral, 7 - 14 Weeks): 10 %(m) Oral Experimental result,

Kev study

Ethanol, 2-(2-NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental

result. Kev study butoxyethoxy)-

NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Propane

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Butane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

NOAEL (Rat(Female, Male), Oral, 103 Weeks): >= 500 mg/kg Oral Read-

across from supporting substance (structural analogue or surrogate), Key

Experimental result, Key study

Glycine, N,N'-1,2ethanediylbis[N-

(carboxymethyl)-, sodium

salt (1:4)

2,6-Octadienal, 3,7-

LOAEL (Rat(Male), Inhalation, 1 - 5 d): 30 mg/m3 Inhalation Read-across from supporting substance (structural analogue or surrogate), Key study

LOAEL (Rat(Female, Male), Oral, 104 - 105 Weeks): 210 mg/kg Oral

Experimental result, Key study

dimethyl-

LOAEL (Rat(Female), Oral, 14 Weeks): 335 mg/kg Oral Experimental result,

NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Ethanol, 2-butoxy-

Experimental result, Key study

NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key

study

NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation

Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Ethanol in vivo (Rabbit): Not irritant Experimental result, Key study

SDS US - RE1000038701



Revision Date: 06/11/2019

Ethanol, 2-(2- in vivo (Rabbit): Not irritant Experimental result, Supporting study

butoxyethoxy)-

Glycine, N,N'-1,2- in vivo (Rabbit): Not irritant Experimental result, Key study

ethanediylbis[N-(carboxymethyl)-, sodium salt (1:4)

Ethanol, 2-butoxy- in vivo (Rabbit): Irritating Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Ethanol Rabbit, 1 - 24 hrs: Not irritating

Ethanol, 2-(2- Rabbit, 24 - 72 hrs: Highly irritating

butoxyethoxy)-

Sodium hydroxide Corrosive

(Na(OH)) Rabbit, 2 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide-

Slightly irritating to eyes

Ethanol, 2-butoxy- Rabbit, 24 - 72 hrs: Irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Ethanol Skin sensitization:, in vivo (Guinea pig): Non sensitising Ethanol, 2-(2-Skin sensitization:, in vivo (Guinea pig): Non sensitising

butoxyethoxy)-

Glycine, N,N'-1,2- Skin sensitization:, in vivo (Guinea pig): Non sensitising

ethanediylbis[N-(carboxymethyl)-, sodium salt (1:4)

Ethanol, 2-butoxy- Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.



Revision Date: 06/11/2019

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specified substance(s):

2-Propanol, 2-methyl- Inhalation - dust and mist: Respiratory tract irritation. - Category 3 with

respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Ethanol LC 50 (Pimephales promelas, 96 h): 15.3 g/l Experimental result, Key study

Ethanol, 2-(2- LC 50 (Lepomis macrochirus, 96 h): 1,300 mg/l Experimental result, Key

butoxyethoxy)- study

LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result,

Supporting study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Glycine, N,N'-1,2ethanedivlbis[N- LC 50 (Lepomis macrochirus, 96 h): 121 mg/l Experimental result, Key study

NOAEL (Lepomis macrochirus, 96 h): 88 mg/l Experimental result, Key

(carboxymethyl)-, sodium study

salt (1:4)

study

NOAEL (Pimephales promelas, 96 h): 961 mg/l Experimental result, Key

LC 50 (Pimephales promelas, 96 h): > 961 mg/l Experimental result, Key

study

Quaternary ammonium compounds, C12-14-

2-Propanol, 2-methyl-

EC 50 (96 h): < 10 mg/l

SDS US - RE1000038701



Revision Date: 06/11/2019

alkyl[(ethylphenyl)methyl] dimethyl, chlorides

2.6-Octadienal, 3.7dimethylLC 50 (Leuciscus idus, 96 h); 6.78 mg/l Experimental result. Key study

Sodium hydroxide

(Na(OH))

LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 125 mg/l Mortality LC 50 (Gambusia affinis, 96 h): < 180 mg/l Experimental result, Supporting

study

Ethanol, 2-butoxy-

LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key

study

Ammonium hydroxide

((NH4)(OH))

LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 15 mg/l Mortality LC 50 (Fathead minnow (Pimephales promelas), 48 h): 7 mg/l Mortality

Aquatic Invertebrates Product:

No data available.

Specified substance(s):

Ethanol

LC 50 (Ceriodaphnia dubia, 48 h): 5,012 mg/l Experimental result, Key study

Ethanol, 2-(2butoxyethoxy)- LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting

study

Butane

LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Glycine, N,N'-1,2ethanediylbis[N-

(carboxymethyl)-, sodium

salt (1:4)

EC 50 (Daphnia magna, 24 h): 610 mg/l Experimental result, Key study

2-Propanol, 2-methyl-

NOAEL (Daphnia magna, 48 h): 180 mg/l Experimental result, Key study EC 50 (Daphnia magna, 48 h): 933 mg/l Experimental result, Key study

Quaternary ammonium compounds, C12-14alkyl[(ethylphenyl)methyl]

dimethyl, chlorides

EC 50: 0.015 mg/l

2,6-Octadienal, 3,7-

dimethyl-

EC 50 (Daphnia magna, 48 h): 6.8 mg/l Experimental result, Key study

Sodium hydroxide

(Na(OH))

EC 50 (Water flea (Ceriodaphnia dubia), 48 h): 34.59 - 47.13 mg/l

Intoxication

Ethanol, 2-butoxy-

EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study

Ammonium hydroxide

((NH4)(OH))

LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 0 - 10 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Ethanol NOAEL (Oryzias latipes): 7,900 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study



Revision Date: 06/11/2019

Glycine, N,N'-1,2ethanediylbis[N-(carboxymethyl)-, sodium salt (1:4)

NOAEL (Danio rerio): >= 25.7 mg/l Read-across from supporting substance

(structural analogue or surrogate), Key study

2-Propanol, 2-methyl-

NOAEL (Clarias gariepinus): 332 mg/l Experimental result, Key study

Quaternary ammonium compounds, C12-14alkyl[(ethylphenyl)methyl] dimethyl, chlorides

NOEC (28 d): 0.032 mg/l

Ethanol, 2-butoxy-

NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

. Ethanol LC 50 (Daphnia magna): 454 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 9.6 mg/l Experimental result, Key study

Glycine, N,N'-1,2ethanediylbis[N-

(carboxymethyl)-, sodium

salt (1:4)

NOAEL (Daphnia magna): 25 mg/l Read-across from supporting substance

(structural analogue or surrogate), Key study

EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study Ethanol, 2-butoxy-

EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Ethanol 95 % Detected in water. Experimental result, Key study

Ethanol, 2-(2butoxyethoxy)- 85 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Glycine, N,N'-1,2ethanediylbis[N-

(carboxymethyl)-, sodium

salt (1:4)

90 - 100 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study

2-Propanol, 2-methyl-2.6 - 5.1 % (29 d) Detected in water. Experimental result, Key study



Revision Date: 06/11/2019

2,6-Octadienal, 3,7-

dimethyl-

85 - 95 % (28 d) Detected in water. Experimental result, Key study

Ethanol, 2-butoxy-

90.4 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Ethanol Cyprinus carpio, Bioconcentration Factor (BCF): 4.5 Aquatic sediment Read-

across from supporting substance (structural analogue or surrogate),

Lepomis macrochirus, Bioconcentration Factor (BCF): 1.8 Aquatic sediment

Supporting study

Glycine, N,N'-1,2-

ethanediylbis[N-(carboxymethyl)-, sodium

Experimental result, Key study

salt (1:4)

2,6-Octadienal, 3,7-

dimethyl-

Bioconcentration Factor (BCF): 89.72 Aguatic sediment Estimated by

calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Ethanol No data available. Ethanol, 2-(2- No data available.

butoxyethoxy)-

Propane No data available.
Butane No data available.
Glycine, N,N'-1,2- No data available.

ethanediylbis[N-

(carboxymethyl)-, sodium

salt (1:4)

2-Propanol, 2-methyl
Quaternary ammonium

No data available.

No data available.

compounds, C12-14-alkyl[(ethylphenyl)methyl]di

methyl, chlorides

2,6-Octadienal, 3,7- No data available.

dimethyl-

Sodium hydroxide (Na(OH)) No data available. Ethanol, 2-butoxy- No data available. Ammonium hydroxide No data available.

((NH4)(OH))

Other adverse effects: No data available.

13. Disposal considerations



Revision Date: 06/11/2019

Disposal instructions: Wash before disposal. Dispose to controlled facilities.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): –
Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): -

EmS No.:

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): –

Packing Group: –

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):



Revision Date: 06/11/2019

Chemical Identity	Reportable quantity
Ethanol	lbs. 100
Propane	lbs. 100
Butane	lbs. 100
2-Propanol, 2-methyl-	lbs. 100
Sodium hydroxide	lbs. 1000
(Na(OH))	
Ammonium hydroxide	lbs. 1000
((NH4)(OH))	

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable aerosol

Serious Eye Damage/Eye Irritation

Skin sensitizer

Specific Target Organ Toxicity - Repeated Exposure

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical iden	<u>ntity</u>	Reportable quai	ntity
Ethanol		lbs. 100	_
Ethanol,	2-(2-		
butoxyethoxy)-			
Propane		lbs. 100	
Butane		lbs. 100	
2-Propanol, 2-r	methyl-	lbs. 100	
Sodium	hydroxide	lbs. 1000	
(Na(OH))			
Ethanol, 2-buto	oxy-		
Ammonium	hydroxide	lbs. 1000	
((NH4)(OH))			

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Ethanol	10000 lbs
Ethanol, 2-(2-butoxyethoxy)-	10000 lbs
Propane	10000 lbs
Butane	10000 lbs
Glycine, N,N'-1,2-ethanediylbis[N-	10000 lbs
(carboxymethyl)-, sodium salt	
(1:4)	
2-Propanol, 2-methyl-	10000 lbs
Quaternary ammonium	10000 lbs
compounds, C12-14-	
alkyl[(ethylphenyl)methyl]dimethyl,	
chlorides	
2,6-Octadienal, 3,7-dimethyl-	10000 lbs
Sodium hydroxide (Na(OH))	10000 lbs
Ethanol, 2-butoxy-	10000 lbs
Ammonium hydroxide	10000 lbs
((NH4)(OH))	
CADA 212 (TDI Donortina)	

SARA 313 (TRI Reporting)

<u>Chemical Identity</u> <u>Reporting</u> <u>Reporting threshold for</u>



Revision Date: 06/11/2019

threshold for other users N230 lbs manufacturing and processing
N230 lbs.

Ethanol, 2-(2-butoxyethoxy)-

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Ethanol

Ethanol, 2-(2-butoxyethoxy)-

Propane

Butane

US. Massachusetts RTK - Substance List

Chemical Identity

Glycine, N,N-bis(carboxymethyl)-, sodium salt (1:3)

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Ethanol

Ethanol, 2-(2-butoxyethoxy)-

Propane

Butane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable



Revision Date: 06/11/2019

Inventory Status:

Austrália AICS: Not in compliance with the inventory.

Canada DSL Inventory List: Not in compliance with the inventory.

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: Not in compliance with the inventory.

China Inv. Existing Chemical Substances: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: Not in compliance with the inventory.

US TSCA Inventory: Not in compliance with the inventory.

New Zealand Inventory of Chemicals:

On or in compliance with the inventory

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory: Not in compliance with the inventory.

Taiwan Chemical Substance Inventory: On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date: 06/11/2019

Revision Information: No data available.

Version #: 1.0

Further Information: FIFRA: This chemical is a pesticide product registered by the United States

Environmental Protection Agency and is subject to certain labeling

requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The pesticide label also includes other important information, including directions for use.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.